

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 549.99I.001
Product name: LUXPOL 490
UFI: XX5F-D04D-G00Y-40SE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Coating product or related for industrial purpose. Only for professional use.

1.3. Details of the supplier of the safety data sheet

Name: ASTRA VERNICI S.R.L.
Full address: Via Della Industria, 4
District and Country: 24052 Azzano San Paolo (BG)
Italy
Tel.: +39 035 530019
Fax: +39 035 531714
e-mail address of the competent person responsible for the Safety Data Sheet: msds@astravernici.it

1.4. Emergency telephone number

For urgent inquiries refer to:
REPUBLIC OF IRELAND :
National Poisons Information Centre
24 hours per day and 365 days a year
01 837 9964
01 809 2566

UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND :
National Health Service (NHS)
Telephone number: 111
Emergency number : 999

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains: MALEIC ANHYDRIDE May produce an allergic reaction.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor.
P370+P378	In case of fire: Use dry chemical or CO2 to extinguish.

Contains:

ISOBUTYL METHYL KETONE
STYRENE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
STYRENE		
INDEX 601-026-00-0	35 $\leq$ x < 40	Flam. Liq. 3 H226, Repr. 2 H361d, Acute Tox. 4 H332, STOT RE 1 H372, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: D LC50 Inhalation vapours: 11,8 mg/l/4h
EC 202-851-5		
CAS 100-42-5		
REACH Reg. 01-2119457861-32-xxxx		

SECTION 3. Composition/information on ingredients ... / >>

ISOBUTYL METHYL KETONE

INDEX 606-004-00-4 2,62 ≤ x < 2,6563

Flam. Liq. 2 H225, Carc. 2 H351, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
LC50 Inhalation vapours: 11 mg/l/4h

EC 203-550-1

CAS 108-10-1

REACH Reg. 01-2119473980-30-xxxx

ETHYL ACETATE

INDEX 607-022-00-5 0,09 ≤ x < 0,1

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

CAS 141-78-6

REACH Reg. 01-2119475103-46-xxxx

2-METHOXY-1-METHYLETHYL ACETATE

INDEX 607-195-00-7 0,06 ≤ x < 0,08

Flam. Liq. 3 H226

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29-xxxx

DIPROPYLENE GLYCOL MONOMETHYL ETHER

INDEX 252-104-2 0,03 ≤ x < 0,05

Substance with a community workplace exposure limit.

EC 34590-94-8

CAS 34590-94-8

REACH Reg. 01-2119450011-60-xxxx

MALEIC ANHYDRIDE

INDEX 607-096-00-9 0,01 ≤ x < 0,02

Acute Tox. 4 H302, STOT RE 1 H372, Skin Corr. 1B H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1A H317, EUH071
LD50 Oral: 400 mg/kg

EC 203-571-6

CAS 108-31-6

REACH Reg. 01-2119463268-32-xxxx

ETHYL METHYL KETONE

INDEX 606-002-00-3 0 < x < 0,01

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 201-159-0

CAS 78-93-3

REACH Reg. 01-2119457290-43-xxxx

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice / attention.

SECTION 4. First aid measures ... / >>

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

SECTION 7. Handling and storage ... / >>

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

2-METHOXY-1-METHYLETHYL ACETATE

Store in an inert atmosphere, sheletered from moisture because it hydrolises easily.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

SECTION 8. Exposure controls/personal protection ... / >>

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	308	50			SKIN
TLV	CZE	270	43,74	550	89,1	SKIN
AGW	DEU	310	50	310	50	11
MAK	DEU	310	50	310	50	
TLV	DNK	309	50			SKIN E
VLA	ESP	308	50			SKIN
VLEP	FRA	308	50			SKIN
TLV	GRC	600	100	900	150	
AK	HUN	308	50			
GVI/KGVI	HRV	308	50			SKIN
VLEP	ITA	308	50			SKIN
RD	LTU	308	50	450	75	SKIN
VLE	PRT	308	50			SKIN
NDS/NDSch	POL	240		480		SKIN
TLV	ROU	308	50			SKIN
MV	SVN	308	50			SKIN
ESD	TUR	308	50			SKIN
WEL	GBR	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH			50			

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
TLV	CZE	270	49,14	550	100,1	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
TLV	DNK	275	50	550	100	SKIN E
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
TLV	GRC	275	50	550	100	
AK	HUN	275	50	550	100	
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
RD	LTU	250	50	400	75	SKIN
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
MV	SVN	275	50	550	100	SKIN
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

SECTION 8. Exposure controls/personal protection ... / >>

STYRENE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	85		215		
TLV	CZE	100	23,1	400	92,4	
AGW	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
TLV	DNK			105 (C)	25 (C)	SKIN
VLA	ESP	86	20	172	40	
VLEP	FRA	100	23,3	200	46,6	
TLV	GRC	425	100	1050	250	
AK	HUN	86	20	172	40	
GVI/KGVI	HRV	430	100	1080	250	SKIN
RD	LTU	90	20	200	50	SKIN
NDS/NDSch	POL	50		100		
TLV	ROU	50	12	150	35	
ПДК	RUS	10		30		n
MV	SVN	86	20	344	80	
ESD	TUR		100		200 (C)	
WEL	GBR	430	100	1080	250	
TLV-ACGIH		10		20		

ETHYL METHYL KETONE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	590		885		
TLV	CZE	600	200,4	900	300,6	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
TLV	DNK	145	50	900	300	SKIN E
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
TLV	GRC	600	200	900	300	
AK	HUN	600	200	900	300	SKIN
GVI/KGVI	HRV	600	200	900	300	
VLEP	ITA	600	200	900	300	
RD	LTU	600	200	900	300	
VLE	PRT	600	200	900	300	
NDS/NDSch	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
ПДК	RUS	200		400		n
MV	SVN	600	200	900	300	SKIN
ESD	TUR	600	200	900	300	
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

SECTION 8. Exposure controls/personal protection ... / >>

ISOBUTYL METHYL KETONE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	50		200		
TLV	CZE	80	19,2	200	48	SKIN
AGW	DEU	83	20	166	40	SKIN
MAK	DEU	83	20	166	40	SKIN
TLV	DNK	83	20	208	50	SKIN E
VLA	ESP	83	20	208	50	
VLEP	FRA	83	20	208	50	
TLV	GRC	410	100	410	100	
AK	HUN	83	20	208	50	
GVI/KGVI	HRV	83	20	208	50	
VLEP	ITA	83	20	208	50	
RD	LTU	83	20	208	50	
VLE	PRT	83	20	208	50	
NDS/NDSch	POL	83		200		
TLV	ROU	83	20	208	50	
ПДК	RUS			5		n
MV	SVN	83	20	208	50	SKIN
ESD	TUR	83	20	208	50	
WEL	GBR	208	50	416	100	SKIN
OEL	EU	83	20	208	50	
TLV-ACGIH		82	20	307	75	

ETHYL ACETATE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	734	200	1468	400	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
TLV	DNK	540	150	1468	400	E
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
RD	LTU	500	150	1100 (C)	300 (C)	
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
ПДК	RUS	50		200		n
MV	SVN	734	200	1468	400	
ESD	TUR	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

SECTION 8. Exposure controls/personal protection ... / >>

MALEIC ANHYDRIDE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1				
TLV	CZE	1	0,245	2	0,49	
AGW	DEU	0,081	0,02	0,081	0,02	11
MAK	DEU	0,081	0,02	0,081 (C)	0,02 (C)	C = 0,20 mg/m3
TLV	DNK	0,4	0,1			
VLA	ESP	0,4	0,1			
VLEP	FRA			1		
TLV	GRC	1				
AK	HUN	0,08	0,2	0,08	0,2	
GVI/KGVI	HRV	0,41	0,1	0,8	0,2	INHAL
GVI/KGVI	HRV	0,41	0,1	0,8	0,2	SKIN
RD	LTU	1,2	0,3	2,5	0,6	
NDS/NDSch	POL	0,5		1		SKIN
TLV	ROU	1	0,25	3	0,75	
ПДК	RUS			1		n + a, A
MV	SVN	0,41	0,1	0,41	0,1	
ESD	TUR	1	0,25			
WEL	GBR	1		3		
TLV-ACGIH		0,01	0,0025			INHAL

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

STYRENE

STIRENE: Adopted Biological Exposure Indices (BEIs) - ACGIH (2012): Determinant 1: Mandelic acid plus phenylglyoxylic acid in urine / Sampling Time: End of shift / BEI@: 400 mg/g. / Notation: Ns = Nonspecific - Determinant 2: Styrene in venous blood / Sampling Time: End of shift / BEI@: 0,2 mg/L. / Notation: Sq = Semi-quantitative - Determinant 3: Toluene in urine / Sampling Time: End of shift / BEI@: 0,03 mg/g. / Notation: none - Determinant 4: o-Cresol in urine / Sampling Time: End of shift / BEI@: 0,3 mg/g. creatinine / Notation: B = Background

ETHYL METHYL KETONE

METILETILCHETONE: Adopted Biological Exposure Indices (BEIs) - ACGIH (2012): Determinant: MEK in urine / Sampling Time: End of shift end of workweek / BEI@: 40 mg/L / Notation: B =Background, NS = Nonspecific

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

SECTION 8. Exposure controls/personal protection ... / >>

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.
Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	dense liquid	
Colour	yellowish	
Odour	solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable liquid	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	23 ≤ T ≤ 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Kinematic viscosity	> 20,5 mm ² /s	Temperature: 20 °C
Dynamic viscosity	75"	Method:Ford Cup 4
		Remark:100 cc.
		Temperature: 20 °C
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,07	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	58,47 %		
VOC (Directive 2010/75/EU)	41,53 %	- 444,37	g/litre
VOC (volatile carbon)	37,68 %	- 403,18	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

STYRENE

Polymerises at temperatures above 65°C/149°F.Fire hazard.Possibility of explosion.

Added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

ETHYL METHYL KETONE

SECTION 10. Stability and reactivity ... / >>

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

ISOBUTYL METHYL KETONE

Reacts violently with: light metals. Attacks various types of plastic materials.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

STYRENE

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, di-tert-butyl peroxide, oxidising substances, oxygen.

ETHYL METHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

ISOBUTYL METHYL KETONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

STYRENE

Avoid contact with: oxidising substances, copper, strong acids.

ETHYL METHYL KETONE

Avoid exposure to: sources of heat.

ISOBUTYL METHYL KETONE

Avoid exposure to: sources of heat.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

STYRENE

Incompatible materials: plastic materials.

ETHYL METHYL KETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

ISOBUTYL METHYL KETONE

Incompatible with: oxidising substances, reducing substances.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, chlorosulphuric acid.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

SECTION 11. Toxicological information ... / >>

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

STYRENE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

STYRENE

The acute toxicity by inhalation at 1000 ppm affects the central nervous system with headache and dizziness, lack of coordination; irritation of the eye and respiratory tract mucous membranes occurs at 500 ppm. Chronic exposure causes depression of the central and peripheral nervous system with loss of memory, headache and drowsiness starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis; dermatosis. Repeated exposure, at low doses of inhaled substance, causes irreversible changes to hearing and may cause changes in colour vision. No certain data is available on the reversibility of the visual impairment. Repeated skin exposure causes irritation. The substance degreases the skin, which can cause dryness and cracking.

Interactive effects

STYRENE

The metabolism of the substance is inhibited by ethanol. When styrene is photo-oxidised with ozone and nitrogen dioxide, as in the formation of smog, products highly irritating for the human eye may ensue.

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat

STYRENE

LD50 (Oral):	5000 mg/kg Rat
LC50 (Inhalation vapours):	11,8 mg/l/4h Rat

ETHYL METHYL KETONE

LD50 (Dermal):	6480 mg/kg Rabbit
LD50 (Oral):	2737 mg/kg Rat
LC50 (Inhalation vapours):	23,5 mg/l/8h Rat

ISOBUTYL METHYL KETONE

LD50 (Dermal):	> 16000 mg/kg Rabbit
LD50 (Oral):	2080 mg/kg Rat
LC50 (Inhalation vapours):	11 mg/l/4h

MALEIC ANHYDRIDE

LD50 (Dermal):	610 mg/kg Rat
LD50 (Oral):	400 mg/kg Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

SECTION 11. Toxicological information ... / >>

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

MALEIC ANHYDRIDE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

STYRENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2002).

Classified as "probable carcinogen" by the US National Toxicology Program (NTP) - (US DHHS, 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water

> 10000 mg/l

Rapidly degradable

STYRENE

Solubility in water

320 mg/l

Rapidly degradable

ETHYL METHYL KETONE

Solubility in water

> 10000 mg/l

Rapidly degradable

SECTION 12. Ecological information ... / >>

ISOBUTYL METHYL KETONE
 Solubility in water > 10000 mg/l
 Rapidly degradable

ETHYL ACETATE
 Solubility in water > 10000 mg/l
 Rapidly degradable

MALEIC ANHYDRIDE
 Solubility in water > 10000 mg/l
 Entirely degradable

12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL ETHER
 Partition coefficient: n-octanol/water 0,0043

2-METHOXY-1-METHYLETHYL ACETATE
 Partition coefficient: n-octanol/water 1,2

STYRENE
 Partition coefficient: n-octanol/water 2,96
 BCF 74

ETHYL METHYL KETONE
 Partition coefficient: n-octanol/water 0,3

ISOBUTYL METHYL KETONE
 Partition coefficient: n-octanol/water 1,9

ETHYL ACETATE
 Partition coefficient: n-octanol/water 0,68
 BCF 30

MALEIC ANHYDRIDE
 Partition coefficient: n-octanol/water -2,78

12.4. Mobility in soil

STYRENE
 Partition coefficient: soil/water 2,55
 ISOBUTYL METHYL KETONE
 Partition coefficient: soil/water 2,008

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
 Waste transportation may be subject to ADR restrictions.
 The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.
 CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT
IMDG: PAINT
IATA: PAINT

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 lt	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

STYRENE

REACH Reg.: 01-2119457861-32-xxxx

Point 75

HYDROQUINONE

REACH Reg.: 01-2119524016-51-xxxx

Point 75

ISOBUTYL METHYL KETONE

REACH Reg.: 01-2119473980-30-xxxx

SECTION 15. Regulatory information ... / >>

Point	75	ETHYL ACETATE
		REACH Reg.: 01-2119475103-46-xxxx
Point	75	MALEIC ANHYDRIDE
		REACH Reg.: 01-2119463268-32-xxxx

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

SECTION 16. Other information ... / >>**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website

SECTION 16. Other information ... / >>

- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 12.